

AM-15

15 Gallon Air Assisted Misting Machine

PREMIUM SPECIFICATIONS. INDUSTRY INNOVATION. VERSATILITY DISCOVERED.

The AM-15 is a versatile foam or misting unit with effective droplets at 15 microns and overall capacity provides superior productivity for large area disinfection. The unit will out perform the commonly used handheld machines on the market today. The large 15 gallon tank provides continual usage - a one stop chemical source. Fill it and disinfect your entire facility.



A Draws from pre-mixed disinfection chemical

B Discharge hose can be up to 100 ft.

C See through 15 gallon tank

D On-board air compressor

E Standard hand mister shown below



APPLICATIONS:

The Pacific AM-15 Air Assisted Misting Machine is a powerful, consistent, and versatile unit for nearly every surface. Use for daily disinfecting of floors, walls, ceilings and more

- Hallways, Banquet areas, Rooms
- Patient rooms
- Classrooms, Weight rooms, Locker rooms, Restrooms
- Health clubs
- Transportation
- Class A office buildings
- Supermarkets, Carts
- Municipalities
- Sports & Recreational complexes



FEATURE

SPECIFICATIONS

MODEL:	AM-15
TECHNICAL SPECIFICATIONS	
Power type	Electricity
Chemical pickup type	Draws from pre-mixed solution
Number of products unit can draw from	One product
Suction line length/diameter	3/8 in. (9.5 mm) inside diameter
Capacity	15 gallons (56.8 liters)
Discharge line length/diameter	25 ft. (7.6 m) coiled twin-line tubing 1/4 in. (6.4 mm outside diameter)
Discharge wand/tip type	Handheld double-barrel misting wand with one nozzle or Polypropylene trigger handle with misting nozzle
Output distance	3-4.5 ft. (0.9-1.4 m)
Output volume	8.9 oz./min (263.2 mL/min) at 50 psi (3.4 bar)
Flow rate*	8.9 oz./min (263.2 mL/min) at 50 psi (3.4 bar)
Pump seals	Santoprene, Viton, or Kalrez
Power cable	9 ft.
Run time from full tank**	Approx. 3.5 hours
Noise level (dBA)	60
Nozzle type	Pneumatic fog nozzle
Number of nozzles	1 nozzle
Droplet size	15 microns at 50 psi (3.4 bar)
Wheel type	Two 10 in. (25.4 cm) non-marking wheels Two 5 in. (12.7 cm) casters with lock
Machine weight	90 lbs.

* Dilution rates and flow rates given are based on chemical with viscosity of water and factory air pressure settings.

** Area Covered and run time may vary based on humidity, air flow, and product used.

DISTRIBUTED BY:



624 Comanche Trl,
Frankfort, KY 40601

(502) 382-8320



GENUINE SERVICE PARTS

PURPOSE BUILT™ TO PROVIDE MAX PERFORMANCE

Why buy a copy when you can get the original parts—the ones actually used in the machine's original design work the best. Not only do you get maximum performance, but you also reduce hassle and downtime. Be sure to contact Pacific Floorcare or a local authorized distributor when you need authentic service parts.



PACIFIC®
FLOORCARE