

S-24XM

24" / 610 mm SCRUBBER

PREMIUM SPECIFICATIONS. INDUSTRY FIRST TECHNOLOGIES. AFFORDABLE PRICE.

The 24-inch / 610 mm scrubber is Purpose Built® to match your cleaning needs. The S-24XM (extreme maneuverability) is a smaller, budget-friendly scrubber that is great for tight spaces and aisles while still maximizing your cleaning path.

A 1,2,3-step training graphics on the control panel!

B Clean on your schedule with sound levels down to 63 dBa

C Don't kneel or strain your back with automatic brush on/off system

D Industry-highest rpm greatly enhances cleaning



AUTOMATED BATTERY PROTECTION SYSTEM

Available on all S-Series scrubbers



S-24XM

APPLICATIONS:

The S-24XM disk scrubber is a highly flexible tool for your cleaning regimen. The large, robust tanks and batteries combined with a compact scrub deck is Purpose Built® for:

- Daily scrubbing of medium sized facilities
- Spill clean-up & water recovery
- Narrow-to-medium width hallways
- Use on uneven floors (dual-disk head)
- Small-to-medium rooms and areas
- Grout and porous floor scrubbing



PACIFIC
FLOOR CARE

FEATURES

SPECIFICATIONS

MODEL:	S-24XM Disk
SOLUTION DELIVERY SYSTEM	
Solution capacity:	11 gal / 42 l
Solution control: (standard)	0 - .5 gpm / 0-1.9 lpm Variable knob adjustment
Solution control: (with chemical injection)	NA
SCRUBBING SYSTEM	
Cleaning path:	24 in / 610 mm
Pad/brush size:	(2) 12 in / 305 mm
Productivity (per hour) - theoretical max:	26,400 ft ² / 2,453 m ²
Productivity (per hour) - average coverage rate*:	17,325 ft ² / 1,610 m ²
BRUSH DRIVE SYSTEM	
Brush motor horsepower:	1.0 hp / 750 W
Brush rpm:	360 rpm
Brush/pad pressure:	60 & 90 lb / 27 & 41 kg
Brush/pad attachment/removal:	Automatic on/off
RECOVERY SYSTEM	
Recovery tank accessibility:	Full cleanout access
Recovery tank capacity:	13 gal / 49 l (2 gal / 7.6 l demisting chamber)
Vacuum motor:	.51 hp / 380 W, 2-stage
Vac motor cfm / cmm:	68 cfm / 1.9 cmm
Vac motor water-lift:	46 in / 117 cm
Standard / narrow aisle squeegee width:	30 in/NA / 76 cm/NA
DRIVE SYSTEM	
Drive type:	Transaxle drive
Motor horsepower:	.25 hp / 187 W
BATTERY SYSTEM	
System voltage:	24 V
Battery amp hour rating:	(2) 12V: 130 AH (wet) / 105 AH (MF)
Battery run time:	Up to 3.5 hours
Charger description:	On-board (standard) Off-board (optional)
MACHINE SPECIFICATIONS	
Product length:	48 in / 122 cm
Product width (without squeegee):	26 in / 66 cm
Product height:	43 in / 109 cm
Product weight (with batteries):	410 lb / 186 kg
Sound level (operator's ear):	63 dBA
Construction:	Rotationally-molded polyethylene tanks, powder coated steel frame
WARRANTY	
Rotationally-molded tanks:	10 years
Parts (excluding wear items):	3 years
Labor:	1 year

*Productivity calculations utilize key factors from the ISSA 540 cleaning times handbook

Note: Specifications subject to change without notice



GENUINE SERVICE PARTS PURPOSE BUILT® TO PROVIDE MAX PERFORMANCE

Why buy a copy when you can get the original parts – the ones actually used in the machine's original design work the best. Not only do you get maximum performance, but you also reduce hassle and downtime. Be sure to contact Pacific Floorcare or a local authorized distributor when you need authentic service parts.

Kentucky Cleaning Solutions, LLC, DBA

BLUEGRASS 
JAN/SAN & PAPER SUPPLIES, LLC

624 Comanche Trail, Frankfort, KY 40601
www.BluegrassJanitorial.com
502-382-8320