

# Durabrite®

## Low Maintenance Finish

### FEATURES

- Extremely durable and mark-resistant finish for low maintenance applications
- High gloss acrylic polymers stay clean, clear, and shiny to reduce maintenance
- Non-yellowing, low maintenance formula offers superb black mark and scuff resistance
- Ideal for reduced burnishing programs (once per week)
- Use on vinyl tile, rubber, linoleum, terrazzo and quarry tile floors
- Excellent seal properties
- Fast-drying – 20 to 30 minutes under normal conditions
- Fast-curing – 2 hours under normal conditions
- Slip-resistant – UL Classified

### PROPERTIES

**Type:** Metal-Interlocked Acrylic

**Form:** Opaque Liquid

**Odor:** Bland

**Color:** Milky White

**pH:** 8.1 - 8.3

**V.O.C.:** <260 gm/l

**Weight per Gallon:** 8.60 Lbs


**Storage Stability:** Min. 1 Year

**Freeze/Thaw:** Passes 3 Cycles

**Film Clarity:** Clear

**Floor Solids:** 18%

Properties are typical and subject to usual manufacturing tolerances



# 253FF

© 2021 Essential Industries, Inc. B0821  
Lit. # LT-90000S253FF



Scan QR code  
for access to more  
product information  
and Safety Data Sheet.

