# PC 9C Duck Pro® by Shurtape®



# PC 9C DUCK PRO® BY SHURTAPE® GENERAL PURPOSE GRADE, COLORED CLOTH DUCT TAPE

#### TYPICAL APPLICATIONS

- For general purpose use in industrial, plumbing, carpet, color-coding, poly hanging and splicing applications, as well as home and general repair applications, particularly where a discreet fix is needed
- For temporary or permanent use, offers 30-day indoor clean removal.

#### **PRODUCT FEATURES**

- General Purpose, contractor grade, colored cloth duct tape
- Conformable
- Cold temperature adhesion
- Will not twist or curl during application
- Hand-tearable
- Waterproof backing
- 30-day indoor, clean removal

#### CONSTRUCTION

Backing: Polyethylene film with a cloth carrier Adhesive: Natural rubber adhesive

#### STANDARD WIDTHS

1.88 in; 2.83 in 48 mm; 72 mm

# STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### **APPLICABLE STANDARDS**

Tested in accordance with UL 723

## STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS			
Green	Beige	Blue	Yellow
(GRN)	(BEI)	(BLU)	(YEL)
Olive	Burgundy	Brown	Orange
(OLV)	(BRG)	(BRN)	(ORG)
Red (RED)	Black (BLK)	White (WHI)	

PHYSICAL PROPERTIES	STANDARD	METRIC
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Elongation	20%	20%
Service Temperature Range	35 F to 200 F	2 C to 93 C
Tensile	26 lbs/in width	45.5 N/10 mm
Thickness - Nominal	9.0 mils	0.23 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user's method determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.





